



Perforated Ceiling Tiles

Gyprock Perforated Ceiling Tiles have a white vinyl laminate finish and provide superior sound absorption for acoustic control in commercial grid ceilings. Perforated Ceiling Tiles are square edged, 13mm thick and available as 1200 x 600mm tiles to suit common exposed grid systems. The acoustic properties of the tiles are achieved by a regular grid of 6mm, full depth holes to approximately 10% of the panel area. This, combined with suitable insulation, provides a medium level of sound absorption to reduce echoes and reverberation. The edges of the tiles are cut square to suit exposed grid ceiling systems. The white vinyl facing is easy to clean.

Recommended Use

- Standard suspended grid systems for interior ceiling applications
- Commercial environments where sound absorption is required such as shopping centres, offices, restaurants, libraries, and galleries.


Perforated Ceiling Tile Specifications	
Feature	Description
Thickness	13mm
Widths	600mm
Lengths	1200mm
Edge	Square
Mass	10kg/m ²
Fire Hazard Properties ^Δ	Group No = 1 SMOGRARC <100 m ² /s ²
Combustibility [◇]	Plasterboard may be used wherever a non-combustible material is required.

^Δ In accordance with AS ISO 9705 and AS 5637.1

[◇] In accordance with NCC2022 Vol 1 Clause C2D10(6)(a) and NCC2019 Amdt1 Vol Clause C1.9(e)(i).



Product Features



Drop-in Tile

Suitable for suspended grid systems



Acoustic

Perforated for enhanced acoustic absorption



Easy to Clean

Vinyl facing for easy cleaning



Australian Made and Owned

Licensed by Australian Made Campaign Ltd



Storage

Protect plasterboard from weather and moisture. Avoid products sagging by storing horizontally, supported on a level platform or full-width support members spaced at max. 600mm centres.

Health and Safety

For further information refer to the Safety Data Sheet for this product which is available from www.gyprock.com.au or contact:

CSR Gyprock
Trinity 3, 39 Delhi Rd, North Ryde NSW 2113
Australia Phone: **131 744**
New Zealand Phone: **0800 277 123**

Installing to Standards

Installing to Standards AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.

Resources

For further information on this product please visit www.gyprock.com.au or refer to the Gyprock Red Book. For technical support, contact:

Manufactured For Life Warranty

Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system. Gyprock continues to lead the market with premium quality products which are the preferred choice of plastering professionals. Gyprock plasterboard products are manufactured to the Australian Standards AS2588 providing confidence in quality of product and support. For details on our product warranty, please log onto www.gyprock.com.au/warranty, or contact us on **1300 306 556**.



Licensed by Australian Made Campaign Limited to use the Australian Made Logo.



Gyprock plasterboard products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.

DESIGNLINK™

PHONE: 1800 621 117