

PRODUCT DATA SHEET



Gyptone Access Panels blend almost imperceptibly into the ceiling with a perforation pattern that matches each of the Gyptone perforated boards. Gyptone Access Panels are designed to allow easy access for inspection and maintenance of services located above the Gyptone perforated plasterboard acoustic ceilings.

Gyptone Access Panels are available in each of the four Gyptone board patterns. The access panels consist of a plasterboard frame that is easily set into the ceiling and a 510mm x 510mm hatch piece with a matching perforation pattern that fits neatly into the frame.

Recommended Use

- Integration into Gyptone acoustic ceilings to allow for inspection, service and maintenance work on installations in the space above.
- Applications where a high level of acoustic performance is required such as theatres, restaurants, shopping centres and hotel foyers.

| Gyptone Access Panel Specifications | | |
|-------------------------------------|--|--|
| Feature | Description | |
| Frame | 600mm x 600mm | |
| Hatch | 510mm x 510mm | |
| Frame Weight | 0.9kg | |
| Hatch Weight | 3.6kg | |
| Fire Hazard | Group No = 1 | |
| Properties [∆] | SMOGRARC <100 m ² /s ² | |
| Combustibility [♦] | Plasterboard may be used wherever a non- | |
| | combustible material is required. | |

 $^{^{\}Delta}$ In accordance with AS ISO 9705 and AS 5637.1



Product Features



Aesthetics

Maintains the seamless look



Acoustics

Absorbs sound into the ceiling to prevent reverberation



Easy Maintenance

Allows access for maintenance



Activ'Air Technology

Uses Activ'Air technology for cleaner air



International Alliance

Delivered through the International Alliance Program



[♦] In accordance with NCC2022 Vol 1 Clause C2D10(6)(a) and NCC2019 Amdt1 Vol Clause C1.9(e)(i).



PRODUCT DATA SHEET



Gyprock offers an access panel solution for each pattern profile in the Gyptone range that provides easy access and integrates seamlessly into the ceiling. Refer to TABLE 1.

| Table 1: Matching Access Panels for Gyptone Perforated Plasterboard | | |
|--|---|--|
| Panel Description | Matching Access Panel Description | |
| Gyptone 12mm Hexagon (63) | Gyptone BT Access Hatch 12 Hexagon (63) | |
| Gyptone 12mm Square (41) | Gyptone BT Access Panel 12 Square (41) | |
| Gyptone 12mm Square Minigrid (47) | Gyptone BT Access Panel 12 Minigrid (47) | |
| Gyptone Slotted Minigrid (6) | Gyptone BT Access Panel Slotted Minigrid (6) | |

Product Manufacture

Gyptone Access Panels are manufactured for CSR Gyprock by worldwide plasterboard specialist Saint-Gobain.

Storage

Protect plasterboard from weather and moisture. Avoid products sagging by storing horizontally, supported on a level platform or full-width support members spaced at max. 600mm centres.

Installing to Standards

Installing to Standards AS/NZS2589: Gypsum linings Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.

For further information refer to the Safety Data Sheet for this product which is available from www.gyprock.com.au or contact:

CSR Gyprock Triniti 3, 39 Delhi Rd, North Ryde NSW 2113

Australia Phone: 131 744

New Zealand Phone: 0800 277 123

Resources

For further information on this product please visit www.gyprock.com.au or refer to the Gyprock Red Book. For technical support, contact:



PHONE: 1800 621 117



products to the Australian construction industry.

Through the International Alliance program, Gyprock seeks to develop exclusive relationships with leading manufacturers throughout the world to deliver the best technologies and