

Gyprock Shaft Liner MP

Shaft Liner MP has a glass fibre-reinforced core encased in a heavy duty linerboard. This enables it to resist fire and make it ideal for use as part of a fire rated wall system. These panels offer exceptional acoustic insulation properties and are used in Gyprock Party Wall, Shaft Wall and StrataWall systems. Shaft Liner MP panel is manufactured with a powerful but gentle antifungal agent that permeates the plasterboard core, as well as the face and back paper of the board, providing enhanced protection against the possibility of mould growth during the early stages of construction. Gyprock Shaft Liner MP Panel can be identified by its blue coloured face paper.

Recommended Use

- Central fire barrier for Party Wall, Shaft Wall and StrataWall systems
- New commercial construction in which mould resistance is necessary
- Commercial applications in which a fire-rated system is required along with enhanced acoustic properties such as multi-residential unit walls, intertenancy walls and party walls, lift wells, stairwells and service shafts.


Gyprock Shaft Liner MP Specifications

Feature	Description
Thickness	25mm
Widths [□]	600mm
Lengths [□]	3000mm/3600mm
Edge Profiles	Square Edge
Paper Colour	Blue
Mass	19.8kg/m ²
Thermal Resistance	0.14 m ² K/W
Fire Hazard Properties ^Δ	Group No = 1 SMOGRARC <100 m ² /s ²
Combustibility [◇]	Plasterboard may be used wherever a non-combustible material is required.
Total Recycled Content	9.3%

[□]Stocked sizes and widths may vary by region, please refer to the relevant product page on gyprock.com.au for details.

^ΔIn accordance with AS ISO 9705 and AS 5637.1

[◇]In accordance with NCC2022 Vol 1 Clause C2D10(6)(a) and NCC2019 Amdt1 Vol Clause C1.9(e)(i)



Product Features



Powerful Antifungal Agent

Resists mould and mildew



Fire-rated

Maintains fire resistance levels around penetrations



Acoustic Properties

Exceptional acoustic insulation properties to help combat sound transmission



Australian Made

Licensed by Australian Made Campaign Ltd



Manufacturing Tolerances

Nominal Thickness	25mm +/- 0.5mm
Nominal Widths	600mm +/- 3mm
Nominal Lengths	From 3000mm and 3600mm +/- 5mm, typically in 300mm increments
Squareness	Cut ends +/- 3mm in the width of the board

**Subject to reasonable manufacturing variance.

Storage

Protect plasterboard from weather and moisture. Avoid products sagging by storing horizontally, supported on a level platform or full-width support members spaced at max. 600mm centres.

Health and Safety

For further information refer to the Safety Data Sheet for this product which is available from www.gyprock.com.au or contact:

CSR Gyprock
Triniti 3, 39 Delhi Rd, North Ryde NSW 2113
Australia Phone: **131 744**
New Zealand Phone: **0800 277 123**

Installing to Standards

Installing to Standards AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.

Resources

For further information on this product please visit www.gyprock.com.au or refer to the Gyprock Red Book. For technical support, contact:

DESIGNLINK™

PHONE: 1800 621 117

Manufactured For Life Warranty

Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system. Gyprock continues to lead the market with premium quality products which are the preferred choice of plastering professionals. Gyprock plasterboard products are manufactured to the Australian Standards AS2588 providing confidence in quality of product and support. For details on our product warranty, please log onto www.gyprock.com.au/warranty, or contact us on **1300 306 556**.



Licensed by Australian Made Campaign Limited to use the Australian Made Logo.



Verified by an independent conformity assessment body to meet the environmental, health and social/ethical criteria of the GECA Panel Boards standard.



Gyprock plasterboard products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.