



## Freshtone™ Ceiling Tiles

Gyprock Freshtone Ceiling Tiles are lightly textured, premium quality plasterboard ceiling tiles that provide acoustic separation in commercial applications. Freshtone Ceiling Tiles are square edged, 10mm thick and available as 1200 x 600mm tiles to suit standard exposed grid systems. The tiles are vinyl-faced, making them easy to clean, durable and resistant to fading and mould growth. Freshtone has a Gyprock Supaceil core to provide sag resistance and longevity. Freshtone tiles are available in Diamond White, known as Arctic White in WA.

### Recommended Use

- Standard suspended grid systems for ceiling applications
- Commercial projects and areas that require moisture resistance such as shopping centres, offices, restaurants, factories, warehouses, and rest rooms.


Freshtone Ceiling Tile Specifications	
Feature	Description
Thickness	10mm
Widths	600mm
Lengths	1200mm
Colour	Diamond White /Arctic White-WA/Black
Surface Finish - Visible	Vinyl laminate
Surface Finish - back	Paper
Edge	Square
Mass	7.2kg/m <sup>2</sup>
CAC	35
Fire Hazard Properties <sup>Δ</sup>	Group No = 1 Average Specific Extinction = Less than 250m <sup>2</sup> /kg
Combustibility <sup>◇</sup>	Plasterboard may be used wherever a non-combustible material is required.

<sup>Δ</sup> In accordance with AS ISO 9705 and AS 5637.1

<sup>◇</sup> In compliance with NC2022 S7C4 1(b) and 2



### Product Features



#### Drop-in Tile

Suitable for suspended grid systems



#### Easy to Clean

Vinyl facing for easy cleaning



#### Wet Area

Moisture resistant properties.



#### Australian Made

Licensed by Australian Made Campaign Ltd



## Storage

Protect plasterboard from weather and moisture. Avoid products sagging by storing horizontally, supported on a level platform or full-width support members spaced at max. 600mm centres.

## Handling

Ensure all surfaces are clean from dust and dirt before unpacking and installation. All ceiling tiles should be handled with clean hands or gloves to prevent soiling of tile face during handling and installation. When removing tiles from the pack, lift the panels from opposite ends rather than dragging panels, to avoid potential damage to the surface. If panels are removed after initial installation, they should be taken completely out of the grid and stored on a flat surface.

## Cleaning

Dust, vacuum or wipe with a damp cloth to clean surface of tile. To minimise the need for significant cleaning, ensure ceiling tiles are unpacked and installed in a clean environment that is clear of dust and dirt.

## Health and Safety

For further information refer to the Safety Data Sheet for this product which is available from [www.gyprock.com.au](http://www.gyprock.com.au) or contact:

CSR Gyprock  
Trinity 3, 39 Delhi Rd, North Ryde NSW 2113  
Australia Phone: **131 744**  
New Zealand Phone: **0800 277 123**

## Installing to Standards

Installing to Standards AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.

## Resources

For further information on this product please visit [www.gyprock.com.au](http://www.gyprock.com.au) or refer to the Gyprock Red Book. For technical support, contact:

**DESIGNLINK™**

PHONE: 1800 621 117

## Manufactured For Life Warranty

Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system. Gyprock continues to lead the market with premium quality products which are the preferred choice of plastering professionals. Gyprock plasterboard products are manufactured to the Australian Standards AS2588 providing confidence in quality of product and support. For details on our product warranty, please log onto [www.gyprock.com.au/warranty](http://www.gyprock.com.au/warranty), or contact us on **1300 306 556**.



Licensed by Australian Made Campaign Limited to use the Australian Made Logo.



Gyprock plasterboard products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.