


Product Data Sheet

# Gyprock HD Screw



The Gyprock HD Screw is specifically designed for use on Gyprock high density plasterboards to achieve a professional finish.

## Product Overview

Featuring a unique lipped head and reversed thread pattern, the Gyprock HD Screw has the ability to drive through boards with ease and achieve a high-quality finish, with less chance of paper burring or bulging around the head.

Collated in durable plastic strips, the HD Screw is ideal for contractors in both residential and commercial settings to install Gyprock high density plasterboard products efficiently to a professional standard.

The Gyprock HD Screw removes the need to pre-drill pilot holes into high density plasterboards and reduces the risk of 'mushrooming' or 'volcanoing' around the head of screws allowing for easier, high quality installations.

## Typical Applications

The Gyprock HD Screw is specifically designed for use on Gyprock high density plasterboards and can be used for both Timber and Steel substrates.

- 10mm Soundchek – Softwood/Hardwood Walls
- 10mm Soundchek – Steel (0.5-0.8 BMT) Walls and Ceilings
- 10mm Superchek – Softwood/Hardwood Walls
- 10mm Superchek – Steel (0.5-0.8 BMT) Walls and Ceilings
- 13mm Soundchek – Steel (0.5-0.8 BMT) Walls and Ceilings

Download the **Gyprock HD Screw product flyer** for more information.



## **Manufactured for Life**

Gyprock plasterboard products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.