

Product Data Sheet

Gyprock Drywall Masonry Adhesive 100



Gyprock Drywall Masonry Adhesive 100 is specially formulated for Western Australian conditions. It is used for adhering plasterboard to masonry and concrete surfaces.

Product Overview

Gyprock Drywall Masonry Adhesive 100 is a simple and convenient way to adhere plasterboard sheets to masonry and concrete walls. It is specially formulated to offer excellent adhesion properties.

Gyprock Drywall Masonry Adhesive 100 is supplied as a dry powder and is easy to mix and apply by hand using a small broadknife. It has an extended 100 minute working life once mixed which allows for larger batches to be mixed for bigger projects.

Typical Applications

Gyprock Drywall Masonry Adhesive 100 is ideal for adhering plasterboard sheets to masonry and concrete substrates.



Superior Adhesion

Good initial grab and excellent adhesion properties



Easy Application

Easy to mix and apply



Defined Setting Time

Extended 100 minute working life

Technical Specifications

Product Options

Drywall Masonry Adhesive 100 is available in 20kg bags with a shelf life of 1 year from date of manufacture.

For product availability and to place an order, contact your nearest supplier.

Physical & Chemical Properties

Specific gravity (H ₂ O=1)	2.3 -2.4
VOC content (as specified by GBCA)	< 10g/L as VOC content per material

Product Manufacture

Gyprock Drywall Masonry Adhesive 100 is manufactured by CSR Gyprock in Australia to stringent product specifications.

Product Handling

Transportation and manual handling: Refer to the Gypsum Board Manufacturers of Australia (GBMA) website for recommended OH&S practices.

Storage: Store bags of compound in a dry environment, protected from the weather and out of direct sunlight. Tear bag open from top corner to dispense compound. Unused product which has been mixed with water should be discarded. Unused product in powder format should be stored in original bag: roll the top of the bag to loosely seal, and store in an airtight container.

Health and Safety

Safety Data Sheets are important documents in the construction industry and assist in the continuing focus on occupational health and safety on and off sites.

Installation Instructions

Installing to Standards

AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.

Resources

Gyprock makes available [resources](#) that provide comprehensive selection, design, installation and maintenance guidance.



Manufactured for Life

Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.



GECA Accredited

Verified by an independent conformity assessment body to meet the environmental, health and social/ethical criteria of the GECA Adhesives, Fillers & Sealants standard.



Certified Low VOC

Exceeds the GBCA specification for Volatile Organic Compound content according to independent testing.