

Product Data Sheet

DIY Cornice Cement



Gyprock DIY Cornice Cement is used for fixing Gyprock cornice at wall and ceiling junctions where the substrate is plasterboard or fibre cement. It is also used for finishing cornice joints and mitres.

Product Overview

DIY Cornice Cement is a setting type compound rather than a drying type that provides superior adhesion with good initial grab and high bond strength. It is available in powder form and is mixed with water to a workable paste with a working life of 50 - 60 minutes.

Typical Applications

DIY Cornice Cement is typically used to install cornice between plasterboard walls and ceilings. It is also suitable for repairing existing cornice and cornice joints and is easily applied with a small broadknife.



Superior Adhesion

Good initial grab and excellent adhesion properties



Easy Application

Applied with a broadknife



DIY Range

Professional quality in convenient pack sizes

Technical Specifications

Product Options

Gyprock DIY Cornice Cement is available in 2.5kg bags with a shelf life of 1 year from date of manufacture.

For product availability and to place an order, contact your nearest supplier.

Physical & Chemical Properties

Specific gravity (H ₂ O=1)	2.3-2.4
VOC content (as specified by GBCA)	< 10g/L as VOC content per material

Product Manufacture

Gyprock DIY Cornice Cement is manufactured by CSR Gyprock in Australia to stringent product specifications.

Product Handling

Transportation and manual handling: Refer to the Gypsum Board Manufacturers of Australia (GBMA) website for recommended OH&S practices.

Storage: Store bags of compound in a dry environment, protected from the weather and out of direct sunlight. Tear bag open from top corner to dispense compound. Unused product which has been mixed with water should be discarded. Unused product in powder format should be stored in original bag: roll the top of the bag to loosely seal, and store in an airtight container.

Health and Safety

Safety Data Sheets are important documents in the construction industry and assist in the continuing focus on occupational health and safety on and off sites.

Installation Instructions

Installing to Standards

AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.

Resources

Gyprock makes available [resources](#) that provide comprehensive selection, design, installation and maintenance guidance.



Manufactured for Life

Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.



GECA Accredited

Verified by an independent conformity assessment body to meet the environmental, health and social/ethical criteria of the GECA Adhesives, Fillers & Sealants standard.



Certified Low VOC

Exceeds the GBCA specification for Volatile Organic Compound content according to independent testing.