

Product Data Sheet

DIY Rapid Patch

Gyprock Rapid Patch is a fast setting dry powder-based compound used for repairing holes, nicks and cracks in plasterboard, fibre cement, timber and masonry.

Product Overview

Once mixed with water, Rapid Patch forms a smooth, fast setting paste, with a working life of around 20 minutes, ideal for filling small cracks and dents with minimal shrinkage. It dries and is ready for sanding in around 40 minutes.

It is a low VOC dry powder compound manufactured by Gyprock in Australia to stringent product specifications.

Typical Applications

Rapid Patch is suitable for repairs to walls and ceilings in both residential and commercial construction where plasterboard, fibre cement timber or masonry is used. It can also be used as an all-purpose compound for setting plasterboard joints.



Australian Made

Licensed by Australian Made Campaign Ltd



Rapid Setting

To allow for sanding and painting soon after application



Repairs

Used for repairs and maintenance



DIY Range

Professional quality in convenient pack sizes

Technical Specifications

Product Options

Gyprock Rapid Patch is available in 2 kg bags with a shelf life of 1 year from date of manufacture.

For product availability and to place an order, contact your **nearest supplier**.

Physical & Chemical Properties

Specific gravity (H ₂ O=1)	2.3-2.4
VOC content (as specified by GBCA)	2g/L as VOC content per material

Product Manufacture

Gyprock Rapid Patch is manufactured by CSR Gyprock in Australia to stringent product specifications.

Product Handling

Transportation and manual handling: Refer to the **Gypsum Board Manufacturers of Australia (GBMA) website** for recommended OH&S practices.

Storage: Store bags of compound in a dry environment, protected from the weather and out of direct sunlight. Tear bag open from top corner to dispense compound. Unused product which has been mixed with water should be discarded. Unused product in powder format should be stored in original bag: roll the top of the bag to loosely seal, and store in an airtight container.

Health and Safety

Safety Data Sheets are important documents in the construction industry and assist in the continuing focus on occupational health and safety on and off sites.

Installation Instructions

Installing to Standards

AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature



Australian Made

Licensed by Australian Made Campaign Limited to use the Australian Made Logo.



Manufactured for Life

Gyprock plasterboard products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.



GECA Accredited

Verified by an independent conformity assessment body to meet the environmental, health and social/ethical criteria of the GECA Adhesives, Fillers & Sealants standard.

Resources

Gyprock makes available **resources** that provide comprehensive selection, design, installation and maintenance guidance.