

Product Data Sheet

Easy-Flow™



Gyprock Easy-Flow is lightweight all-purpose jointing compound specially developed for mechanical application, with excellent tape adhesion, trowelling and feathering properties.

Product Overview

Easy-Flow is a versatile all-purpose jointing compound used for all coats in a three coat jointing system. This low VOC formulation is available in a convenient premixed form that has been developed to provide exceptional out-of-machine flow for mechanical application.

Each coat dries and hardens in approximately 24 hours ready for recoating or sanding.

Typical Applications

Gyprock Easy-Flow is typically used for each coat in a three coat jointing system in residential and commercial walls and ceilings. It is specifically designed for application with mud boxes, automatic tapers and other machine tools.



All-purpose

Use for all coats of a 3 coat joint system



Pre-mixed

Quick to prepare, easy to apply



Exceptional Flow

Ideal for machine application

Technical Specifications

Product Options

Gyprock Easy-Flow is available in the following pack size:

Pack	15kg Pail (12.5L approx.)
Coverage - Tape & Second Coat	23kg/100m ²
Coverage - Topping Coat	7kg/100m ²

Shelf life is 1 year from manufacture

For product availability and to place an order, contact your nearest supplier.

Physical & Chemical Properties

Specific gravity (H ₂ O=1)	1.1 - 1.5
VOC content (as specified by GBCA)	<10 g/L as VOC content per material

Product Manufacture

Gyprock Easy-Flow is manufactured by CSR Gyprock in Australia to stringent product specifications.

Product Handling

Transportation and manual handling: Refer to the Gypsum Board Manufacturers of Australia (GBMA) website for recommended OH&S practices.

Storage: Store buckets of compound in a dry environment out of direct sunlight. Remove lid and stir prior to use. Unused product should be stored by resealing the original bucket. Remix prior to use. Discard if drying has commenced.

Health and Safety

Safety Data Sheets are important documents in the construction industry and assist in the continuing focus on occupational health and safety on and off sites.

Installation Instructions

Installing to Standards

AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.

Resources

Gyprock makes available [resources](#) that provide comprehensive selection, design, installation and maintenance guidance.



Manufactured for Life

Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.



GECA Accredited

Verified by an independent conformity assessment body to meet the environmental, health and social/ethical criteria of the GECA Adhesives, Fillers & Sealants standard.



Certified Low VOC

Exceeds the GBCA specification for Volatile Organic Compound content according to independent testing.