



Product Data Sheet

# Paper Tape

Create the strongest joint with Gyprock Paper Tape &ndash; a high tensile, spark perforated tape, laid into the first coat.

## Product Overview

Gyprock Paper Tape is designed to strengthen joints when embedded in the first coat of the jointing system. 50mm wide Paper Tape is creased along the centre line to provide a crisp finish for corners and improved performance in automatic taping tools. Available in 75m and 150m rolls, it has a rough texture for better adhesion and spark perforations to allow the compound to permeate its surface.

## Typical Applications

Gyprock Paper Tape is embedded in the first coat of a three coat jointing system to improve strength and resist cracking in joints and corners.

It's ideal for use on wall and ceiling joints, and can be used in fire rated systems.



### Two Handy Sizes

Catering for both smaller and larger jobs



### Strong

Strengthens joints



### Automatic Taping Tools

Suitable for use in automatic taping tools

## Technical Specifications

### Product Options

Paper Tape is available in two roll sizes:

Width	50mm
Length	75m 150m

For product availability and to place an order, contact your **nearest supplier**.

### Product Manufacture

Paper Tape is manufactured for CSR Gyprock in Australia to stringent product specifications.

## Installation Instructions

### Installing to Standards

AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.



### Manufactured for Life

Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.

### Resources

Gyprock makes available [resources](#) that provide comprehensive selection, design, installation and maintenance guidance.