



Product Data Sheet

## Ultra-AP™



Gyprock Ultra-AP is the ultimate lightweight all-purpose jointing compound with superior tape adhesion and shrinkage. With Ultra-AP you can be confident you are using the best.

### Product Overview

Ultra-AP is a versatile all-purpose jointing compound used for all coats in a three coat jointing system. This low VOC formulation is available in a convenient premixed form that has been developed to provide exceptional tape adhesion. This is combined with excellent sandability when used as a top coat. Its ultra-low shrinkage and fast drying make it ideal for hot and dry conditions.

Each coat dries and hardens in approximately 24 hours ready for recoating or sanding.

### Typical Applications

Gyprock Ultra-AP is typically used for each coat in a three coat jointing system in residential and commercial walls and ceilings. With ultra-strong tape adhesion for tape and second coats, it is ideal for internal angles and, while it can be hand applied, it flows smoothly through mud boxes, automatic tapers and other machine tools.



#### Ultra Strong

Exceptional tape adhesion



#### All-purpose

Use for all coats of a 3 coat joint system



#### Pre-mixed

Quick to prepare, easy to apply

## Technical Specifications

### Product Options

Gyprock Ultra-AP is available in the following pack size:

|                               |                          |
|-------------------------------|--------------------------|
| Pack                          | 15kg Pail (14L approx.)  |
| Coverage - Tape & Second Coat | 18.5kg/100m <sup>2</sup> |
| Coverage - Topping Coat       | 5.2kg/100m <sup>2</sup>  |

Shelf life is 1 year from manufacture.

For product availability and to place an order, contact your nearest supplier.

### Physical & Chemical Properties

|                                       |                                     |
|---------------------------------------|-------------------------------------|
| Specific gravity (H <sub>2</sub> O=1) | 1.0 - 1.4                           |
| VOC content (as specified by GBCA)    | <10 g/L as VOC content per material |

### Product Manufacture

Gyprock Ultra-AP is manufactured by CSR Gyprock in Australia to stringent product specifications.

### Product Handling

**Transportation and manual handling:** Refer to the Gypsum Board Manufacturers of Australia (GBMA) website for recommended OH&S practices.

**Storage:** Store buckets of compound in a dry environment out of direct sunlight. Remove lid and stir prior to use. Unused product should be stored by resealing the original bucket. Remix prior to use. Discard if drying has commenced.

### Health and Safety

**Safety Data Sheets** are important documents in the construction industry and assist in the continuing focus on occupational health and safety on and off sites.

## Installation Instructions

### Installing to Standards

AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.

### Resources

Gyprock makes available [resources](#) that provide comprehensive selection, design, installation and maintenance guidance.



#### Manufactured for Life

Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.



#### GECA Accredited

Verified by an independent conformity assessment body to meet the environmental, health and social/ethical criteria of the GECA Adhesives, Fillers & Sealants standard.



#### Certified Low VOC

Exceeds the GBCA specification for Volatile Organic Compound content according to independent testing.