



Product Data Sheet

Wet Area Acrylic Sealant



Create a long lasting, functional seal with Gyprock Wet Area Acrylic Sealant - paintable, flexible and suitable for wet areas.

Product Overview

Wet Area Acrylic Sealant is white in colour and can also be used as a general purpose gap filler, providing mould and mildew resistance.

It is suitable for use with Hebel, concrete, masonry, brickwork, plasterboard, fibre cement, metal, timber and plastic substrates.

Typical Applications

Suitable for both residential and commercial construction, Wet Area Acrylic Sealant assists in wet area caulking of penetrations and sealing junctions in areas such as pre-formed shower bases, baths and around plumbing penetrations.



Powerful Antifungal Agent

Resists mould and mildew



Paintable

Can be painted over



Wet Area

Moisture resistant properties

Technical Specifications

Product Options

Wet Area Acrylic Sealant is available in a 450g tube and has a shelf life of 1 year from date of manufacture.

For product availability and to place an order, contact your nearest supplier.

Physical and chemical properties

Specific gravity (H ₂ O=1)	Approximately 1.55
VOC content	Trace

Product Manufacture

Wet Area Acrylic Sealant is manufactured for CSR Gyprock in Australia to stringent product specifications.

Product Handling

Transportation and manual handling: Refer to the Gypsum Board Manufacturers of Australia (GBMA) website for recommended OH&S practices.

Storage: Store unopened tubes below 30°C in a cool dry place away from direct sunlight. Opened tubes may skin and form a lump near the opening. Discard any lumps or skin and remaining product can be used.

Health and Safety

Safety Data Sheets are important documents in the construction industry and assist in the continuing focus on occupational health and safety on and off sites.

Installation Instructions

Installing to Standards

AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.



Manufactured for Life

Gyprock plasterboard products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.



Certified Low VOC

Exceeds the GBCA specification for Volatile Organic Compound content according to independent testing.

Resources

Gyprock makes available [resources](#) that provide comprehensive selection, design, installation and maintenance guidance.