



Product Data Sheet

One Finish



Gyprock One Finish is a pre-mixed acrylic compound designed to create a uniform surface on interior plasterboard or fibre cement walls and ceilings affected by critical lighting conditions.

Product Overview

One Finish reduces the difference in porosity, texture and sheen between board and jointing compound, to create a uniform white surface ready for decoration.

Due to its superior hiding power, it can be used as part of a level 5 finish specification under AS/NZS 2589.

Typical Applications

One Finish is rolled or sprayed directly onto the wall or ceiling, eliminating the need for trowel application. It is easy to sand, and where a level of final texture is acceptable, sanding is not required prior to the painting process. A polyester 10-12mm nap is recommended for general roller application, and the product should be allowed to dry for 16-24 hours prior to final painting and decoration. One Finish can also be applied onto already painted surfaces after lightly sanding.



Pre-mixed

Quick to prepare, easy to apply



Smooth Finish

Smooth and easy to sand



Easy Application

Roll or spray-on

Technical Specifications

Product Options

Gyprock One Finish is available in a 20kg bucket with coverage of 5-7m² per kg.

It has a shelf life of 1 year from date of manufacture.

For product availability and to place an order, contact your nearest supplier.

Physical & Chemical Properties

Specific gravity (H ₂ O=1)	1.6-2.0
VOC content (as specified by GBCA)	8g/L as VOC content per material

Product Manufacture

Gyprock One Finish is manufactured for CSR Gyprock in Australia to stringent product specifications.

Product Handling

Transportation and manual handling: Refer to the Gypsum Board Manufacturers of Australia (GBMA) website for recommended OH&S practices.

Storage: Store buckets in a dry environment out of direct sunlight. Remove lid and stir prior to use. Unused product should be stored by resealing the original bucket. Remix prior to use. Discard if drying has commenced.

Health and Safety

Safety Data Sheets are important documents in the construction industry and assist in the continuing focus on occupational health and safety on and off sites.

Installation Instructions

Installing to Standards

AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.



Manufactured for Life

Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.



Certified Low VOC

Exceeds the GBCA specification for Volatile Organic Compound content according to independent testing.

Resources

Gyprock makes available [resources](#) that provide comprehensive selection, design, installation and maintenance guidance.